

tesa® Edge Securing 50533

High adhesion temporary protection tape for freshly painted surfaces

PRODUCT INFORMATION

Product Description

tesa® Edge Securing 50533 consists of an UV-stabilized backing coated with a high adhesion EVA adhesive.

Features & benefits:

- Paint protection during outdoor storage up to 12 months
- Secure adhesion during transport
- Easy disposal - both the film and the adhesive system are environmentally friendly

Main Application

- tesa® Edge Securing 50533 ensures high-strength adhesion and can be used to keep tesa Bodyguard® tapes securely in place, especially in areas of difficult geometries to prevent dust and humidity penetration
- tesa® Edge Securing 50533 is suitable for die-cutting and can be printed on to be used as security, steering or marking label
- tesa® Edge Securing 50533 can also be used as base material for heavy duty protection pads for bumpers and door edges

Technical Data

■ Backing material	polyolefinic film	■ Elongation at break	660 %
■ Total thickness	96 µm	■ Tensile strength	21.5 N/cm
■ Type of adhesive	EVA	■ UV-resistance	52 weeks
■ Adhesion to steel	3 N/cm		

Properties

■ Easy to remove	yes	■ Paint compatibility	++
■ Suitable for die cutting	yes	■ Resistance to chemicals	++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

tesa® Edge Securing 50533 is also available as die cut product solution as tesa® Edge Securing 54533.

For latest information on this product please visit <http://l.tesa.com/?ip=50533>

Page 1 of 1 / As of 07/11/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.